

2316W


Non-woven Double-sided Tape

Technical Data

- Key Features**
 - Excellent initial adhesion.
 - Excellent resistance to high temperature.
 - Good adhesion on film and plastic materials.

- Application Ideas**
 - Adhesive to MARK, film, power switch, foam materials, fabric materials as well as plastic materials.

- Construction**



• Technical Data

Test Item	Unit	Value	Test Method
Thickness	mm	0.16±0.01	ASTM-1000
Initial Adhesion	Ball No.	14#~15#	GB/T4852, Ball tack. J.dow method at room temperature. Tape size: 100mm*150mm.
180° Peel Adhesion	gf/25mm	2250	GB/T2792, 180° peel strength to substrate at room temperature, tape size: 25mm*150mm.
Holding Power	hrs	>24	ASTM D-3654 to the stainless steel, 80°C temperature, 1000g static load.
Temperature Resistance	°C	-20°C~120°C	—
Standard Width	mm	1050	—
Standard Length	m	50	—
Color	White		—
Release Liner	Paper		—

• Shelf Life & Storage Conditions

Tape in roll form: Shelf life 12 months from the date of manufacture when stored in original cartons at 20°C and 50% relative humidity.

Ideal tape application temperature range is 21°C to 38°C.

Notes: The information contained in this data sheet is intended to assist you in designing with Incheng adhesive tape. The technical information and datas should be considered representative or typical only. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose. The user should determine the suitability of Incheng adhesive tape for each application.