

33008HC
PET Film Double-Sided Tape


Technical Data

- Product Description** It uses thin layer of PET film as base material,transparent colloform.Excellent function with steel and plastic surface.

- Key Features** Ultra-thin thickness of only 8µm.
 Good adhesion level relative to low thickness.
 Excellent resistance to demanding environmental conditions.
 Excellent handling performance in converting processes.

- Application Ideas** Used widely for the adhesion of accessories of phone, computer, and panel, etc.
 Fixing of reflection foil to LCD frame
 Splicing of thin plastic films

- Construction**



• Technical Data

Test Item	Unit	Value	Test Method
Thickness	mm	0.008±0.001	
Initial Adhesion	Ball No.	<3#	GB/T4852,Ball tack. J.dow method at room temperature. Tape size: 100mm*150mm.
180° Peel Adhesion	N/25mm	3	GB/T2792,180°peel strength to substrate at room temperature,tape size:25mm*150mm
Holding Power	SUS	hrs	> 12
	PET	hrs	> 12
Color	Transparent		-
Release Liner	Transparent release liner		-

• **Environment
Resistance**

Temperature Range -10°C~80°C

Weather Resistance Normal

• **Shelf Life & Storage
Conditions**

Tape in roll form: Shelf life 12 months from the date of manufacture when stored in original cartons at 20°C and 50% relative humidity.

Ideal tape application temperature range is 21°C to 38°C.

Notes: The information contained in this data sheet is intended to assist you in designing with Incheng adhesive tape. The technical information and data should be considered representative or typical only. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose. The user should determine the suitability of Incheng adhesive tape for each application.

深圳仁盛化成材料技术有限公司

Incheng Chemical Co., Ltd



Tel: (+86)755-86962203

Fax: (+86)20-38892205

www.incheng.net