


3305CD4

PET Film Double-Sided Removable Tape

Technical Data

- Product Description**
 3305CD4 double sided removeable tape is coated with adhesive on both sides, one side mounts permanently, one side is repositionable/removable.
- Key Features**
 Excellent function with steel and plastic panel.
 Good adhesion to general foam.
 Easy application to a curved surface.
 No residue on substrate when remove.
- Application Ideas**
 Widely used in electronics, electrical appliances (refrigerator, air conditioning , stickers, washing machine , paste) , toys , handicrafts , plastic , PVC , PP, PET, printed matter, cardboard products .
- Construction**



Technical Data

Test Item	Unit	Value	Test Method
Thickness	mm	0.055	ASTM-1000
Adhesive Strength	gf/25mm	1000/50	ASTM D-3330
Shear Strength	gf/cm ²	>5000	ASTM D-1002
Temperature Resistance	°C	120	To Stainless Steel Panel, PET film, 80°C Temperature, No residue on substrate

Shelf Life & Storage Conditions

Tape in roll form: Shelf life 12 months from the date of manufacture when stored in original cartons at 20°C and 50% relative humidity.

Ideal tape application temperature range is 21°C to 38°C.

Notes: The information contained in this data sheet is intended to assist you in designing with Incheng adhesive tape. The technical information and datas should be considered representative or typical only. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose. The user should determine the suitability of Incheng adhesive tape for each application.

深圳仁盛化成材料技术有限公司

Incheng Chemical Co., Ltd



Tel: (+86)755-86962203

Fax: (+86)20-38892205

www.incheng.net