

A4030BC

Acrylic Foam Tape

Technical Data

• Product Description

A4030BC is a double side thin acrylic foam tape , which is widely used in a range of electronic industry,accessary and Automotive applications.


• Key Features

Hight adhesion & strong cohesion.
 Moisture-proof,solvent resistance.
 Good performance for high and low temperature periodically cycles.
 Good performance for bonding various fixing and die-cutting
 Low-acid.
 Good resistance to demanding environmental conditions.
 Double side release,good performance for die-cutting.

• Application Ideas

Good performance to bond TP module to LCM,LCD + PC panel, and mobile phone window fixing

• Construction



• Technical Data

Test Item	Unit	Value	Test Method	
Thickness	mm	0.3 ± 0.03	ASTM-1000	
Color	--	Gray or Black	--	
Release Liner	--	PET or Paper	--	
Standard Size	mm×m	900 × 33	--	
Peel Adhesion	SUS	gf/25mm	≥2000	300mm/Min, KSA 1107
	PC		≥1800	300mm/Min, KSA 1107
Holding Power	1 hrs	25mm*25mm for 1kg weight	KSA 1107	
Temperature Resistance	Short term	°C	≥120	--
	Long term		≥100	

● **Application Guidelines**

For maximum bonding result, the application surfaces should be cleaned with a 50:50 mixture (isopropyl alcohol and water). Ideal tape application temperature is ranged from 18°C to 38°C and an excellent bond is allowed to dwell 72 hrs.

● **Shelf Life & Storage Conditions**

18months after purchase and stored in a seal box within indoors condition

Notes: The information contained in this data sheet is intended to assist you in designing with Incheng adhesive tape. The technical information and datas should be considered representative or typical only. It is not intended to and does not create any warranties,express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose.The user should determine the suitability of Incheng adhesive tape for each application.

Incheng Chemical Co., Ltd



Tel: (+86)755-86962203

Fax: (+86)20-38892205

www.incheng.net