

## D60300

### PET Protective Film(D Series)

#### Technical Data

• **Product Description**

It is a single coated PET protective film with clear PET liner.

• **Key Features**

Hight adhesion & Holding power to matte surface.

No adhesive residue.

Good performance for die-cutting.

Excellent resistance to demanding environmental conditions.

Have a high degree of temperature resistance.

• **Application Ideas**

Plastic housing & panting metal housing for LCD , OLED, EL, PDP, Touch-panel, PDA, Printing Film,FPC,etc.

• **Construction**



• **Technical Data**

Test Item	Unit	Value/Result	Test Method	
Thickness	PET Film	mm	0.025	-
	Adhesive	mm	0.035	-
	Total	mm	0.060	-
Peel Force	g/inch	230	ASTM D-3330,To Polycarbonate, 180° Peel	
Temperature Resistance	hrs	120	To Stainlness Steel Panel, PET film, 80°C Temperature,No residue on substrate	
Width	mm	900	-	
Color	Transparent		-	
Release Liner	Clear PET Film		-	

• **Shelf Life & Storage Conditions**

Shelf life 6 months from the date of manufacture when stored in original cartons at 18-25°C and 30-75% relative humidity.

**Notes:** The information contained in this data sheet is intended to assist you in designing with Incheng products. The technical information and data should be considered representative or typical only. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for particular purpose or that the results shown on this data sheet will be achieved by user for a particular purpose. The user should determine the suitability of Incheng adhesive tape for each application.

---

深圳仁盛化成材料技术有限公司

Incheng Chemical Co., Ltd



Tel: (+86)755-86962203

Fax: (+86)20-38892205

[www.incheng.net](http://www.incheng.net)